

Available with actuator function: **POWER OPEN - POWER CLOSE, FAILSAFE, MODULATING, FAILSAFE MODULATING**

VB060M



Overview

The VB060M aluminum housed multi-voltage electric valve actuator from the European electric actuator manufacturer Valbia offers an impressive list of standard features that include multi-voltage capability, protection against damage from over-torque or condensation, and emergency hand operation facility.

Available modulating on request with either 4-20mA or 0-10V input and output, with factory fitted internal positioning system.

Available failsafe on request (except 12V version) with factory fitted internally installed battery back-up system.

VB060M VALBIA Electric Actuator Specifications

Voltage range / Duty rating	Low voltage version	12V AC (1ph) or DC / 50% 24V AC (1ph) or DC / 75%
	High voltage version	100-240V AC (1ph) / 75%
Operating time (0-90° no load)		9 seconds
Maximum break torque		531 lb. Ins (60Nm)
IP Rating (IEC 60529)		Similar to NEMA 4 (IP67 Type 4)
Working angle Standard (on request)		90° (180° & 270° option)
Mounting ISO:5211 x DIN 3337		F05 & F07 x 14 (std)
Motor switches		2 x SPDT micro switches
End of travel confirmation (volt free)		2 x SPDT micro switches
Heater		Yes
Ambient temperature range		-4 to +131°F (-20° to +55°C)
Electrical connections		M20x1.5 x 2
Weight		9.9lbs (4.5 kg)

VB060M Consumption

High Voltage Version	Nominal Voltage	100-240V AC (1 ph 50/60Hz)
	Current	0.3 - 0.6A
	Power	60-72 VA
High Voltage Version	Nominal Voltage	12V AC/DC / 24V AC/DC
	Current 12V / 24V	2.85 - 3.8A / 1.2 - 1.8A
	Power	34 - 46VA / 29 - 43VA
Frequency		50/60Hz


How this VB060M electric 1/4 turn valve actuator works (on-off)

Electrically operated valves are driven by an electric actuator containing a motor and gearbox. On receipt of a continuous voltage signal (not pulse) the motor runs and, via a gearbox in the electric actuator, rotates the valve stem. The motor stops at the desired position (usually 0° or 90°) by an internal cam striking a micro-switch. The valve actuator remains in this position, with the voltage still applied continuously, until switched and a continuous voltage reversing signal (not pulse) is applied, which runs the motor in the opposite direction, reversing the rotation until a separate internal cam strikes a separate micro-switch and stop the motor. The VB060M actuator is designed to have the external power continuously applied, and power must not be switched off when end of travel is achieved.

Available with actuator function: **POWER OPEN - POWER CLOSE, FAILSAFE, MODULATING, FAILSAFE MODULATING**


VB-060M ON - OFF ELECTRIC ACTUATOR

Power open, power close, stays put on loss of external power.




VB-060M MODULATING ELECTRIC ACTUATOR

Proportional control, stays put on loss of external power.



Available with actuator function: **POWER OPEN - POWER CLOSE, FAILSAFE, MODULATING, FAILSAFE MODULATING**

VB060M Dimensions (mm)



ISO5211 Mounting	F05	F07
Mounting PCD (mm)	50	70
Star Drive (Standard)	14mm	
Star Drive (Optional)	11mm or 17mm	

Dimensions (mm):																
CH	A	B	C	D	E	F	G	H	I	L	M	N	O	P	Q	R
14	139	56	35	220	197	63	134	176	16	-	50	70	-	M6x14	M8x15	10